



# AccuStandard<sup>®</sup>, Inc.

125 Market St., New Haven, CT 06513 USA

Tel: 203-786-5290 Fax: 203-786-5287

## SAFETY DATA SHEET

### SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### 1.1 - Product Identifiers

Catalog Name: ASTM-P-135-02

Description: Pour Point, Approx. Value -25 °C

#### 1.2 - Relevant Identified Uses of the Substance or Mixture

Laboratory Chemical Reference Material

#### 1.3 - Supplier Details

Company: AccuStandard, Inc.

125 Market St.

New Haven, CT 06513 USA

Telephone Number: 203-786-5290

Fax: 203-786-5287

Email: edocs@accustandard.com

#### 1.4 - Emergency Telephone Number

Emergency Phone #: AccuStandard, Inc.

1-203-502-7070 (USA)

+001-203-502-7070 (International)

24 hours / 7 days a week

### SECTION 2 - HAZARDS IDENTIFICATION

#### 2.1 - GHS Label Elements



**Signal Word:** Danger

#### **Hazard Codes:**

H227 - Combustible. (Flammable liquids, category 4)

H304 - Aspiration hazard if swallowed - may be fatal if swallowed and enters airways. (Aspiration hazard, category 1)

H336 - Vapors may cause drowsiness and dizziness. (Specific target organ toxicity, single exposure; Narcotic effects, Category 3)

#### **Precautionary Codes:**


P202 - This product should only be used by persons trained in the safe handling of hazardous chemicals.

P210 - Store in a cool place away from ignition sources.

P233 - Store in a tightly closed container. (P404)

P260 - Do not breathe vapor.

P262 - Do not get in eyes, on skin or clothing.



2	HEALTH
1	FLAMMABILITY
0	PHYSICAL HAZARD

**SECTION 2 - HAZARDS IDENTIFICATION** - continued**2.1 - GHS Label Elements** - continued

P264 - Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available.

P284 - Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), or a risk assessment shows air-purifying respirators are appropriate, use of a NIOSH/MSHA approved air supplied respirator is advised. Use a full-face respirator with multi-purpose combination (US) or type ABEK (EN14387) respirator cartridges in absence of proper environmental control. Always use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Engineering and/or administrative controls should be implemented to reduce exposure.

P331 - Ingestion: Do NOT induce vomiting. Call a physician or poison control center immediately. Give victim a glass of water a little at a time. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, lower head below waist to prevent fluid from entering the lungs.

P338 - Eye contact: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers.

P360 - Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

**2.2 - Other Hazards****2.2.1 - Symptom of Exposure Health/Environment**

Combustible. (Flammable liquids, category 4)

Aspiration hazard if swallowed - may be fatal if swallowed and enters airways. (Aspiration hazard, category 1)

Vapors may cause drowsiness and dizziness. (Specific target organ toxicity, single exposure; Narcotic effects, Category 3)

**2.2.2 - Potential Health Effects**

May be irritating to eyes.

May be irritating to skin.

May be harmful if absorbed through the skin. (Acute toxicity, dermal, category 5)

May be harmful if inhaled. (Acute toxicity, inhalation, category 5)

May be harmful if swallowed. (Acute toxicity, oral, category 5)

**2.2.3 - Routes of Entry**

Inhalation, ingestion or skin contact.

**2.2.4 - Carcinogenicity**

This product is or contains a component that is not listed (ACGIH, IARC, NTP, OSHA) as a cancer causing agent.

**SECTION 3 - COMPOSITION / ANALYTES DATA**

Description: Pour Point, Approx. Value -25 °C

Analyte	CAS #	% Concentration	ACGIH -TLV (mg/m³)			OSHA -PEL (mg/m³)		
			TWA	STEL	Skin	TWA	STEL	Skin
Linear Hydrocarbons	N/A	100.000						

**SECTION 4 - FIRST AID MEASURES****4.1 - First Aid Procedures - General**

Get medical assistance for all cases of overexposure.

**SECTION 4 - FIRST AID MEASURES** - continued**4.2 - Eye Contact**

Eye contact: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. (P338)

**4.3 - Skin Contact**

Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse. (P360)

**4.4 - Inhalation**

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

**4.5 - Ingestion**

Ingestion: Do NOT induce vomiting. Call a physician or poison control center immediately. Give victim a glass of water a little at a time. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, lower head below waist to prevent fluid from entering the lungs. (P331)

**SECTION 5 - FIRE FIGHTING MEASURES****5.1 - Flammable Properties**

Containers can build up pressure if exposed to heat.

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

**5.2 - Extinguishing Media**

Use alcohol foam, carbon dioxide, or dry chemical when fighting fires involving this material.

Water spray to cool fire-exposed containers and disperse vapors.

**5.3 - Protection of Firefighters**

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES****6.1 - Spill Response**

Wear a self-contained breathing apparatus and appropriate Personal protection. Prevent contact with skin or eyes. Ventilate area. Stop leak if you can do so without risk. Absorb on sand or vermiculite, take up and containerize for proper disposal. Flush spill area with water. Comply with Federal, State, and local regulations.

**SECTION 7 - HANDLING AND STORAGE**

Store in a tightly closed container. (P404)

Store in a cool place away from ignition sources.

Do not breathe vapor. (P260)

Use with adequate ventilation.

Do not get in eyes, on skin or clothing. (P262)

Avoid prolonged or repeated exposure.

This product should only be used by persons trained in the safe handling of hazardous chemicals. (P202)

**SECTION 8 - EXPOSURE CONTROLS****8.1 - Engineering Controls/PPE**

Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available. (P264)

**8.2 - General Hygiene Considerations**

Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), or a risk assessment shows air-purifying respirators are appropriate, use of a NIOSH/MSHA approved air supplied respirator is advised. Use a full-face respirator with multi-purpose combination (US) or type ABEK (EN14387) respirator cartridges in absence of proper environmental control. Always use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Engineering and/or administrative controls should be implemented to reduce exposure.

Material must be handled or transferred in an approved fume hood or with equivalent ventilation.

Compatible chemical-resistant protective gloves must be worn to prevent skin contact. Inspect gloves prior to use. Use proper glove removal technique to avoid contact with product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash hands thoroughly and dry.

Use eye protection tested and approved under the appropriate government standards such as NIOSH (US) or EN 166 (EU).

All recommendations are advisory only and must be evaluated by an industrial hygienist and/or safety officer familiar with the specific situation of anticipated use, such as concentration and amount of the substance in the workplace. Any recommendation should not be construed as offering an approval for any specific use of the product.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Clear, colorless liquid

Odor: N/A

Odor Threshold: N/A

pH: N/A

Melting Point: -13.9 °F / -25.5 °C

Boiling Point: 384.6 °F / 196 °C

Flash Point: 140 °F (60 °C) (cc)

Evaporation Rate (Butyl Acetate=1): Negligible

Flammability Class: N/A

Lower Flammability Level: 0.6

Upper Flammability Level: 6.5

Vapor Pressure: <0.4 mmHg (20 °C)

Vapor Density (Air = 1): 5.4 g/L

Specific Gravity: 0.740 g/cm<sup>3</sup>

Solubility in Water: Insoluble

Partition Coefficient: N/A

Autoignition Temperature: 464 °F (240 °C)

Decomposition Temperature: N/A

Viscosity: N/A

VOC Content: N/A

Percent Volatile: N/A

**SECTION 10 - STABILITY AND REACTIVITY**

Stability: Stable

Materials to Avoid: Oxidizers  
Bases

Hazardous Decomposition: Oxides of carbon

Hazardous Polymerization: Will not occur

Condition to Avoid: Heat; Contact with ignition sources

**SECTION 11 - TOXICOLOGICAL INFORMATION****Human Health Toxicity**

See section 2 for specific toxicological information for the ingredients of this product.

LD50 (Oral): Rat - >2000 mg/kg

LD50 (Dermal) : Rabbit ->2000 mg/kg

LC50 (Inhalation): Rat - >6.1mg/L 4H

Aspiration hazard if swallowed - may be fatal if swallowed and enters airways. (Aspiration hazard, category 1)

No other information related to the toxicological properties of this product is available at this time.

**SECTION 12 - ECOLOGICAL INFORMATION****Environmental Toxicity**

By complying with sections 6 and 7 there should be no release to the environment.

LC50 (Fish): N/A

EC50 (Aquatic Invertebrate): N/A

BCF: N/A

Readily biodegradable

No other information related to the ecological properties of this product is available at this time.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Recycle or incinerate at any EPA approved facility or dispose in compliance with Federal, State and local regulations. Empty containers must be triple-rinsed prior to disposal.

**SECTION 14 - TRANSPORT INFORMATION****Transportation Information (DOT/IATA)**

UN Number: UN2330

Class: 3

Packing Group: III

Proper Shipping Name: Undecane

Poison by Inhalation: No

Marine Pollutant: No

**SECTION 15 - REGULATORY INFORMATION**

The CAS number of this product is listed on the TSCA Inventory.

This product is NOT subject to SARA section 313 reporting requirements.

**SECTION 15 - REGULATORY INFORMATION** - *continued*

**For laboratory, research and development use only. Not for manufacturing or commercial purposes.**

In addition to federal and state regulations, local regulations may apply. Check with your local regulatory authorities.

**SECTION 16 - OTHER INFORMATION**

This document has been designed to meet the requirements of OSHA, ANSI, GHS and CHIPs regulations. Chemicals are classified using the Globally Harmonized System for Classification and Labeling of Chemicals and CLP Regulation (EC) No. 1272/2008.

The statements contained herein are offered for informational purposes only and are based on technical data that we believe to be accurate. The manufacturer will not assume any liability for the accuracy and completeness of this information. Final determination of the suitability of the material is the responsibility of the user. Although certain hazards are described herein, the user should not presume that these are the only hazards that exist. Since conditions and manner of use are outside of the manufacturers control, we make

**NO WARRANTY OF MERCHANTABILITY, EXPRESSED OR IMPLIED, AND ASSUME NO LIABILITY  
RESULTING FROM ITS USE.**

Legend : N/A = Not Available    ND = Not Determined    NR = Not Regulated

Alteration of any information contained herein without written permission from the manufacturer is strictly prohibited.

**HMIS/NFPA HAZARD INDEX**

- 0 - Minimal
- 1 - Slight
- 2 - Moderate
- 3 - Serious
- 4 - Severe

\* - Additional Hazard

**GHS HAZARD INDEX**

- Category 1 - Most Severe
- Category 5 - Least Severe

\*\*\*\* End of Document \*\*\*\*